

10/530197

PCT/GB 2003 / 0 0 4 2 1 0



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 28 OCT 2003

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely the company to certain additional company law rules.

Signed *Andrew Gensay*
Dated 16 October 2003

BEST AVAILABLE COPY



The
**Patent
Office**

100CT02 E754490-1 D02887
P01/7700 0.00-0223437.5

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference	XA1543		
2. Patent application number (The Patent Office will fill in this part)	0223437.5		
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Alenia Marconi Systems Limited Eastwood House Glebe Road, Chelmsford Essex, CM1 1QW 07948664001 ✓ United Kingdom		
Patents ADP number (if you know it)			
If the applicant is a corporate body, give the country/state of its incorporation	United Kingdom		
4. Title of the invention	IMPROVEMENTS IN OR RELATING TO TARGETING SYSTEMS		
5. Name of your agent (if you have one)			
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	BAE SYSTEMS plc Group IP Department Lancaster House, P.O. Box 87 Farnborough Aerospace Centre Farnborough, Hampshire, GU14 6YU 07914674002 ✓		
Patents ADP number (if you know it)			
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application		Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))	YES		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	05 ✓
Claim(s)	02 ✓
Abstract	01 ✓
Drawing(s)	02 + 2

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

1 ✓

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Margaret Mackett

Date

30 September 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Maria Burkes 01252 383487

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

IMPROVEMENTS IN OR RELATING TO TARGETING SYSTEMS

The present invention relates to targeting systems and is more particularly concerned with a control system for such systems.

In conventional targeting systems, a shell is fired from a barrel towards a target and, depending on where the shell lands, the targeting system is adjusted to improve the accuracy of the position of where the next shell fired lands. This process is repeated until a shell hits the target and then no further adjustment is required as subsequent shells should be on target.

As the time to acquire an exact 'lock' on the target may be protracted, a number of shells may be wasted in the process of acquiring the range to hit the target. This has the consequence of reducing the overall life of the barrel from which the shell is fired.

It is therefore an object of the present invention to provide an improved targeting system which overcomes the disadvantages mentioned above.

In accordance with one aspect of the present invention, there is provided a method of controlling the operation of a missile launcher which fires free fall ballistics missiles, the method comprising the steps of:

- a) firing a missile from the missile launcher;
- b) tracking the trajectory of the fired missile;
- 20 c) calculating a predicted point of impact of the missile after it reaches its trajectory apogee;
- d) feeding back the predicted point of impact to the missile launcher before the missile impacts;
- e) applying a correction prior to firing a subsequent missile; and
- 25 f) repeating steps a) to e) until the missile impacts a chosen target.

Advantageously, step d) comprises feeding back the predicted range of the missile.

In accordance with a second aspect of the present invention, there is provided a control system for a free fall ballistics missile fired from a missile launcher, the control system including:-

5 tracking means for tracking the trajectory of a missile fired from the missile launcher;

calculation means for calculating a predicted point of impact of the missile, the calculation means being operable immediately after the missile reaches its trajectory apogee; and

10 feedback means for feeding back the predicted point of impact to the missile launcher so that a correction can be applied before the fired missile makes impact prior to the launch of subsequent missile.

Advantageously, the calculation means comprises a processor connected to receive data from the tracking means and to provide data relating to the predicted point of impact in the form of range information.

15 It is preferred that the processor includes the feedback means.

In one embodiment of the present invention, the tracking means comprises a tracking radar system which recognises the missile as it is fired from the missile launcher.

20 In accordance with a further aspect of the present invention, there is provided a targeting system including a control system as described above.

For a better understanding of the present invention, reference will now be made, by way of example only, to the accompanying drawings in which:-

Figure 1 illustrates a missile launcher firing a missile towards a target in accordance with the present invention; and

25 Figure 2 is a block diagram of a control system in accordance with present invention.

Referring initially to Figure 1, a target 10 is shown being fired upon by a launcher system 12. For example, the target 10 may comprise a first ship and

the launcher system 12 may be mounted on a platform located on land or on another ship. Only the barrel 14 of the launcher system 12 is shown for clarity.

When the target 10 is determined to be hostile and it is decided to fire on it, the launcher system 12 is positioned so that the barrel 14 is angled in position 14a to fire a shell 16a which follows a trajectory 18a. The trajectory 18a passes through an apogee 20a before splashing down at 22a and misses the ship 10.

In accordance with the present invention, a radar system (not shown) associated with the launcher system 12 tracks the shell 16a as it exits barrel 14a until it reaches the apogee 20a of its trajectory. From the data collected by the radar system up to the apogee 20a, it is possible to calculate the landing position 22a before the shell 16a reaches that position, and hence provide a range correction, ΔR_1 , for the launcher system 12. This range correction effectively moves the barrel 14 to position 14b ready to fire another shell 16b before shell 16a hits position 22a.

Shell 16b follows trajectory 18b and has an apogee at 20b. However, although landing position 22b of shell 16b is nearer the ship 10, a further range correction, ΔR_2 , is required. As before, the further range correction is calculated before shell 16b reaches landing position 22b, and is applied to move the barrel 14 to position 14c ready to fire a further shell 16c before shell 16b hits position 22b.

Shell 16c follows trajectory 18c and has an apogee at 20c. In this case, it is calculated that landing position 22c of shell 16c is coincidental with the ship 10 before shell 16c reaches that position and at least one further shell (not shown) can be directed along substantially the same trajectory as trajectory 18c to impact the ship 10.

Turning now to Figure 2, a block diagram illustrating a control system 30 for launcher 12 of Figure 1 is shown. The control system 30 comprises a target acquisition unit 32 which provides initial targeting instructions for a launcher control unit 34 which launches a shell 16a from a barrel 14 (Figure 1). The launcher control unit 34 is connected to a tracking radar unit 36 and a processor

unit 38. The target acquisition unit 32 is also connected to tracking radar unit 36 and the processor unit 38 as shown.

When the target acquisition unit 32 provides the initial targeting instructions to the launcher control unit 34 via link 40, it provides the same
5 instructions to the tracking radar unit 36 and the processor unit 38 via links 42 and 44 respectively. These instructions establish the starting point from which the tracking radar unit 36 provides data relating to the trajectory of a shell which is launched using those instructions, and from which the processor unit 38 calculates the range correction data for the launcher control unit 34.

10 The launcher control unit 34 provides data relating to the shell (not shown) which is to be launched by the launcher (not shown) to the tracking radar unit 36 over the link 46. This data provides the tracking radar unit 36 with details of how to recognise the shell which it is to track before or as the shell is launched. The launcher control unit 34 also provides data relating to launch of
15 the shell to the processor unit 38 over link 48. Data from the tracking radar unit 36 is fed via link 50 to the processor unit 38, so that the processor unit 38 can calculate the predicted location of the shell impact once the apogee of the trajectory of the shell has been achieved, and provide range correction data for the launcher control unit 34 over link 52.

20 It will be appreciated that once the tracking radar unit 36 has established a settled track on a shell which has been launched from a launcher (not shown) associated with the launcher control unit 34, the data sent to the processor unit 38 from that settled track allows the predicted shell impact location to be determined with some accuracy. The accuracy of the predicted shell impact
25 location will improve as a function of time, and it has been determined that a while after the shell has reached the apogee of its trajectory, the accuracy of the predicted shell impact location is adequate to use as the basis for a feedback signal for the launcher control unit 34 to correct the elevation of the barrel of the launcher. This has the advantage that the predicted range of the shell is
30 known at a time considerably before the shell impacts and the launch control unit 34 can apply a correction to a second shell from a shell which is yet to land.

Moreover, the system of the present invention has the advantage that the number of shells which need to be fired in an engagement, from the start of the engagement to hitting the target, can be substantially reduced. The time involved is also reduced. This, in turn, has the advantage that barrel life of the launcher can be extended in proportion.

5

Although the present invention has been described with reference to determining the landing position of a shell, it will be understood that the invention can be applied to any free fall ballistics missile. Furthermore, the invention can be used with any stationary or relatively slowly-moving target.

CLAIMS

1. A method of controlling the operation of a missile launcher which fires free fall ballistics missiles, the method comprising the steps of:
 - a) firing a missile from the missile launcher;
 - 5 b) tracking the trajectory of the fired missile;
 - c) calculating a predicted point of impact of the missile after it reaches its trajectory apogee;
 - d) feeding back the predicted point of impact to the missile launcher before the missile impacts;
 - 10 e) applying a correction prior to firing a subsequent missile; and
 - f) repeating steps a) to e) until the missile impacts a chosen target.
2. A method according to claim 1, wherein step d) comprises feeding back the predicted range of the missile.
3. A control system for a free fall ballistics missile fired from a missile launcher, the control system including:-
 - 15 tracking means for tracking the trajectory of a missile fired from the missile launcher;
 - calculation means for calculating a predicted point of impact of the missile, the calculation means being operable immediately after the missile reaches its trajectory apogee; and
 - 20 feedback means for feeding back the predicted point of impact to the missile launcher so that a correction can be applied before the fired missile makes impact prior to the launch of subsequent missile.
4. A control system according to claim 3, wherein the calculation means comprises a processor connected to receive data from the tracking means and to provide data relating to the predicted point of impact in the form of range information.
- 25

5. A control system according to claim 4, wherein the processor includes the feedback means.
6. A control system according to any one of claims 3 to 5, wherein the tracking means comprises a tracking radar system.
- 5 7. A control system according to claim 6, wherein the tracking radar system recognises the missile as it is fired from the missile launcher.
8. A targeting system including a control system according to any one of claims 3 to 7.
9. A method of controlling the operation of a missile launcher substantially
10 as hereinbefore described with reference to the accompanying drawings.
10. A control system substantially as hereinbefore described with reference to the accompanying drawings.

ABSTRACT

IMPROVEMENTS IN OR RELATING TO TARGETING SYSTEMS

Described herein is a method of controlling the operation of a missile
5 launcher (12) by predicting the landing position (22) of a missile (16) in flight
before it lands. The method includes tracking the missile (16) as it travels
along its trajectory (18) until it reaches its apogee (20) and calculating the
landing position (22) to provide a feedback correction signal to launcher (12) for
the next missile to be launched. By utilising a feedback correction signal in this
10 way, the time to hitting a target (10) from the time of engagement is
substantially reduced.

(Fig. 1)

1/2




Fig. 1




Fig. 2